

SmartOne Configuration Software Release Notes - November 22, 2019

GLOBALSTAR CONFIDENTIAL AND PROPRIETARY INFORMATION - All data and information contained in this document are confidential and proprietary to Globalstar, Inc. Globalstar reserves the right to make changes in technical and product specifications without prior notice. Copyright© 2019 Globalstar® Incorporated. Globalstar® is a registered trademark of Globalstar Incorporated. All rights reserved.

Description of Release Package contents:

SmartOne-Configuration-Program_3_4_20.exe - Executable file for the SmartOne Configuration Software Program
SmartOne_Configuration_Software_Release_Notes.pdf - This file

SmartOne Configuration Software program Release Notes:

SmartOne Configurator Software v3.4.20 contains:

- Added support for continuous GPS mode for Smartone C devices (devices *must* be line-powered due to increased battery drain)
- Due to added features, updated configuration file extension to .gcfg4
- Removed DFU button from the configuration tool
- Bug Fix: Prevents users from programming airfinder or the Beaconsing mode in non-SmartOneSolar devices
- Bug-Fix: Removed invalid parameter popup when in motion interval is greater than or equal to at-rest interval

SmartOne Configurator Software v3.3.10 contains:

- Added new ESN range for SmartOne C: 4300000-4399999
- Fixed SmartOne Solar programming cable timeout issues.
- Includes new features for only SmartOne Solar:
 - Pin 1 power
 - Beaconsing mode
 - AirFinder
- Authorization code window for enabling Airfinder

SmartOne Configurator Software v3.3.6 contains:

- Upload Firmware button is now enabled after successful DFU over Bluetooth.

SmartOne Configurator Software v3.3.5 contains:

- Upload Firmware button is now available after every Serial DFU.
- Show error dialog if attempting to program Solar-only features to non-Solar devices.
- SmartOne Solar Configuration features are now marked in the User Interface.

SmartOne Configurator Software v3.3.4 contains:

- Change of text for the configuration history.
- Bug Fix - Diagnostic Interval data is properly loaded

SmartOne Configurator Software v3.3.3 contains:

- Bug Fix - Ghosting of the Read window.
- Bug Fix - Bluetooth Reading dialog does not show unnecessarily.
- Text change to "Send message when voltage:" for Wetted Voltage.

SmartOne Configurator Software v3.3.2 contains:

- Text is changed from Closes to $\geq 3V$ and from Opens to $< 3V$ for input 1 and 2.
- Input 1 and 2 types are now mentioned in the View Summary
- Input 1 and 2 tab controls are now synchronized with the Status Changed Message, Undesired State Message and Accumulate Message.
If you change the Type of Input; the SC Message, US Message and Acc Message tabs will change too and vice versa.
- Bug Fixes: Read Time out issue

SmartOne Configurator Software v3.3.1 contains:

- Dry Contact and Wetted Voltage on Input 1 and Input 2
- Warning dialog box upon changing the Speed and Heading settings.
- Clearing or Removing the interval does not clear the ESN list.

SmartOne Configurator Software v3.2.13 contains:

- All the ESNs are now properly added to the Configuration History
- Programming over serial now adds to the Configuration History

Note: History file format changed.

SmartOne Configurator Software v3.2.12 contains:

- Bug Fix - Only programs the selected ESNs

SmartOne Configurator Software v3.2.10 contains:

- Bug Fix - Open Configuration from History (Error Code 103) is now solved.

SmartOne Configurator Software v3.2.9 contains:

- Reliable Programming multiple devices through Serial
- Support for SmartOne B
- Support for older Configuration History files
- Fixed Speed and Heading issue in New Configuration
- UI Bug Fixes.

SmartOne Configurator Software v3.2.8 contains:

- Resume feature in BLE DFU is implemented. Improved reliability.